TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to the field of optical communication systems, and more particularly to a method and apparatus for managing one or more optical elements.

1 10 =

ı nk

BACKGROUND

Optical amplification systems are becoming increasingly complex. For example, the number of channels being amplified continues to increase as the spacing between adjacent wavelengths utilized decreases and new communication bands are implemented. Moreover, as the distance the optical signals traverse increases, the number of optical elements and spans of fiber in each optical link increases.

10

5

As the amplification systems increase in complexity, it becomes increasingly difficult to track and manage the specifics of how each element is provisioned and the operational characteristics of the elements.

10

15

20

25

30

OVERVIEW OF EXAMPLE EMBODIMENTS

The present invention recognizes a need for a method and apparatus operable to facilitate monitoring and/or management of the operation of one or more optical Various implementations the elements. οf present invention reduce or eliminate at least some of the shortcomings of conventional element management approaches.

In one aspect of the invention, a method of managing one or more optical elements comprises storing in a memory, provisioning information describing at least one setting of an optical element and monitored information describing at least one operational characteristic of the optical element. At least a portion of the monitored information is correlated with at least a portion of the provisioning information. The method further comprises maintaining in the memory, а correlation comprising the provisioning information stored over time the monitored information correlated that provisioning information.

In another aspect of the invention, a method of managing one or more optical elements comprises accessing a memory comprising monitored information describing at one operational characteristic of an optical element measured at a plurality of time periods. further comprises provisioning memory information correlated with least of the at some monitored information. The provisioning information describes at least one setting of the optical element. The method comprises retrieving provisioning information correlated with monitored information reflecting desired operational characteristic of the optical

element. In addition, the method comprises applying at least a portion of the retrieved information to an application operable to monitor and/or modify the performance of the optical element based at least in part on the retrieved information.

10

5

15

In yet another aspect of the invention, a system operable to facilitate management of one or more optical elements comprises an element agent operable to receive provisioning information describing at least one setting optical and monitoring information of element an describing at least one operational characteristic of the optical element. At least a portion of the provisioning information is correlated with at least a portion of the monitored information. The system further comprises an element memory accessible to the element agent and operable to maintain a correlation history for the element, the correlation history comprising a plurality of correlated provisioning and monitored information measurements.

10

15

20

25

30

Depending on the specific features implemented, particular embodiments of the present invention may exhibit some, none, or all of the following technical For example, various embodiments of the advantages. invention facilitate maintaining a correlation history including provisioning information correlated monitored information over a period of operation of an optical element, an optical link, or a plurality of optical links. The correlation history can facilitate maintenance and/or operations efficiency various enhancing functions with respect to the element's and/or link's operation.

For example, a graphical user interface (GUI) could display one or more sets of correlated provisioning information and monitored information to facilitate identification of trends in operation, to identify a malfunctioning component of the element, to facilitate optimization of operation, or various other utilities. As another example, the correlation history could facilitate "before and after" comparisons to assess the impact of a change in provisioning to the operation of the element and/or the link.

As still another example, the correlation history facilitate identification of could improper orinefficient provisioning settings in a particular element or link. As a related example, the correlation history could facilitate reversion provisioning. For example, the correlation history could store a set of provisioning information, which is known based, for example, on past experience to yield desired results. By indexing the correlation history using a portion of the provisioning or more desired operational information and one

characteristics, the remaining provisioning information associated with the desired operating characteristics can be recalled and applied to the element and/or the link.

These are just a few examples of advantageous uses of a correlation history in an optical amplification system. Various other uses of this information fall within the spirit and scope of this invention. Other technical advantages are readily apparent to one of skill in the art from the attached figures, description, and claims.

1 4 2

The state of the s

1 1 1

[,,]

5

10

15

20

25

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and for further features and advantages thereof, reference is now made to the following description taken in conjunction with the accompanying drawings, in which:

FIGURE 1 is a block diagram showing an exemplary optical communication system constructed according to the teachings of the present invention;

FIGURE 2 is a block diagram showing one example of an amplification span constructed according to the teachings of the present invention;

FIGURE 3 is a block diagram of one example of a correlation history associated with a particular optical element constructed according to the teachings of the present invention;

FIGURE 4 is a block diagram of a link management system constructed according to the teachings of the present invention;

FIGURE 5 is a block diagram showing one example of a multiple link management system constructed according to the teachings of the present invention; and

FIGURE 6 is a flow chart illustrating one example of a method of managing one or more optical elements according to the teachings of the present invention.

10

15

20

25

30

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

FIGURE 1 is a block diagram showing an exemplary optical communication system 10 operable to facilitate communication of one or more optical signals and to track and/or manage the operation of one or more optical elements in system 10. Optical amplifiers, optical add/drop multiplexers, cross connects, input terminals including optical transmitters, and output terminals including optical receivers provide just a few examples of optical elements that can be monitored and/or managed using system 10.

In this example, system 10 includes an input terminal 11. In the illustrated embodiment, input terminal 11 includes a transmitter bank 12 operable to generate a plurality of wavelength signals (or channels) 16a-16n. Each wavelength signal 16a-16n comprises a wavelength or range of wavelengths of light substantially different from wavelengths carried by other signals 16.

Transmitter bank 12 may include, for example, one or more optical transmitters operable to generate alone or in combination a plurality of wavelength signals 16. In one embodiment, each one of the plurality of transmitters is operable to generate one optical signal having at least one wavelength that is distinct from wavelengths generated by other transmitters 12. Alternatively, a single transmitter 12 operable to generate a plurality of wavelength signals could be implemented.

In the illustrated embodiment, input terminal 11 also includes a combiner 14 operable to receive multiple signal wavelengths 16a-16n and to combine those signal wavelengths into a single multiple wavelength signal 16. As one particular example, combiner 14 could comprise a

10

15

20

25

30

wavelength division multiplexer (WDM). The term wavelength division multiplexer as used herein may include wavelength division multiplexers or dense wavelength division multiplexers.

In this particular example, input terminal 11 further includes a booster amplifier 18 operable to receive and amplify wavelengths of signal 16a in preparation for communication over a communication medium 20. Although this example illustrates input terminal 11 as including each of transmitter bank 12, combiner 14, and booster amplifier 18, one or more of those elements could reside externally to input terminal 11.

System 10 communicates optical signal 16 over an optical communication medium 20. Communication medium 20 can comprise a plurality of spans 20a-20n of fiber, each separated by an optical element. As used in this document, the term "span" refers to an optical medium coupled to one or more optical elements. As particular examples, fiber spans 20 could comprise standard single (SMF), dispersion-shifted fiber mode fiber non-zero dispersion-shifted fiber (NZDSF), or other fiber type or combinations of fiber types.

Two or more spans of medium 20 can collectively form an optical link. As used herein, the term "optical link" refers to a plurality of optical spans coupled to one or more optical elements. In the illustrated example, system 10 includes one link 25. System 10 could alternatively include any number of additional links:

In this example, system 10 also includes one or more in-line amplifiers 22a-22m. In-line amplifiers 22 reside between fiber spans 20 and operate to amplify signal 16 as it traverses fiber 20.

10

15

20

25

30

10

In this example, system 10 includes one or more add/drop multiplexers, switches, and/or routers 15 coupled to communication medium 20 and operable to direct signals to and from optical link 25 for combination with signals to and from other optical links. Element 15 may be coupled to an amplifier or may itself be capable of amplifying optical signals received.

System 10 can also include an output terminal operable to receive signals from communication link 20 and to facilitate, for example, conversion of the optical signals to an electrical format. In this example, output 13 includes a preamplifier 24 operable terminal receive signal 16 from a final fiber span 20n and to amplify signal 16 prior to passing that signal to a separator 26. Separator 26 may comprise, for example, a wavelength division demultiplexer (WDM). Separator 26 operates to separate individual wavelength 16a-16n from multiple wavelength signal 16. Separator 26 can communicate individual signal wavelengths or ranges of wavelengths 16a-16n to a bank of receivers 28 and/or other optical communication paths. Although this example illustrates output terminal 13 as including each of preamplifier 24, separator 26, and receivers 28, one or more of those elements could reside externally to output terminal 13.

Amplifiers within system 10 could each comprise, for example, a rare earth doped amplifier such as an erbium doped or thulium doped amplifier, a Raman amplifier, a semiconductor amplifier, or a hybrid or combination of these or other amplifier types.

At least one optical element in system 10 comprises or communicates with a management system 30 operable to

The factor and factor from the factor factor for the factor facto

5

10

15

20

25

30

track and/or manage the performance of that element or of the optical link containing that element. Management system 30 operates to store provisioning information describing at least one setting of the element and to store monitored information describing at least one operational characteristic of the element. Management system 30 correlates at least some of the provisioning information with at least some of the monitored information and maintains a correlation history useful in a variety of applications.

FIGURE 2 is a block diagram showing one example of an amplification span 100 including an optical element 110 and an element manager 130 operable to track and/or manage the performance of element 110. In this particular example, element 110 comprises input an terminal including a plurality of optical transmitters and a booster amplifier. Although this example describes implementing element manager in combination with an input terminal, element manager 130 could alternatively be used to track and/or manage any other type of optical element in system 10, such as an in-line or other type of amplifier, an output terminal, an add/drop multiplexer, a cross connect, or a router, to name a few.

The booster amplifier of element 110 may comprise any type of amplifier including, for example, a rare-earth doped amplifier, a distributed Raman amplifier, a discrete Raman amplifier, a semiconductor amplifier, or a combination of these or other types of amplifiers. Element 110 couples to optical span 120a, which might comprise, for example, a span of standard single mode fiber, dispersion-shifted fiber, non-zero

10

15

20

25

30

dispersion-shifted fiber, or other fiber type or combinations of fiber types.

Element manager 130 includes an element agent 132 operable to receive provisioning information 140 and monitoring information 142. Provisioning information 140 comprises information describing at least one setting of element 110. For example, provisioning information 140 could comprise information relating to the gain of the preamplifier in element 110, a laser drive current associated with one or more of the transmitters or the preamplifier in element 110, a pre-emphasis associated with element 110, or a number of channels being processed by element 110, to name a few. optical elements may store these or various other items of provisioning information, depending on the particular application of the optical element.

Monitored information 142 comprises information describing at least one operational characteristic of element 110. Monitored information 142 can be obtained at various locations along amplification span 100. example, monitored information 142 may be collected from an input to element 110 or from an output of element 110. Examples of monitored information 142 include power, output mid-stage power, gain tilt, power, signal-to-noise ratio, back reflected power, total transmitted power, per channel transmitted power, total received power, or per channel received power, pump laser laser drive current, power, pump thermal electrical cooler settings, thermal electrical cooler drive currents, to name a few. Of course, the particular monitored information collected can vary depending on the function of the element being monitored. Moreover, other

10

15

20

25

or additional operational characteristics could be monitored without departing from the scope of the invention.

In one particular embodiment, element agent 132 operates to query element 110 to obtain provisioning information 140 and/or monitored information 142. recording provisioning information 140 and/or information 142 only when monitored provisioning characteristics are changed, element agent 132 can periodically, on a random basis, or on command query element 110 to retrieve provisioning information 140 and/or monitored information 142.

Regardless of how or when element agent 132 receives provisioning information 140 and monitored information 142, element agent 132 stores the information received in a memory 134. Memory 134 may comprise, for example, any firmware, software, or combination thereof hardware, facilitate retrieval operable to store and information. Memory 134 can comprise any of a variety of data structures, arrangements, or compilations operable to store and facilitate retrieval of various information. This may include, for example, the use of a dynamic random access memory (DRAM), a static random access memory (SRAM), or any other suitable volatile non-volatile storage and retrieval device a combination of devices. Although, in this embodiment, memory 134 is shown as residing within element manager 130, all or a portion of memory 134 could reside remotely from and accessible to element agent 132.

In the illustrated embodiment, memory 134 includes a correlation history 136. Correlation history 136 may comprise, for example, a memory operable to store

10

15

20

25

30

provisioning information 140 and monitored information 142, where at least a portion of monitored information correlated with at least a 142 portion provisioning information 140. Correlation history 136 plurality of sets of correlated include a provisioning information 140 and monitored information 142 stored over a period of time of operation of element 110.

Memory 134 is accessible to one or more applications 150 operable to monitor, display, report on, analyze, and/or modify the performance of element 110 based at least in part on information retrieved from memory 134.

In operation, element agent 132 receives provisioning information 140 and monitored information 142 correlated with at least a portion of provisioning information 140. In a particular embodiment, element agent 132 may query element 110 to retrieve this information. Element agent 132 may receive provisioning information 140 and correlated monitored information 142 at various times during operation of element 110.

Element agent 132 stores provisioning information 140 and correlated monitored information 142 in memory 134. In a particular embodiment, element agent 132 stores provisioning information 140 and correlated monitored information 142 associated with a particular time period in a record stored in correlation history 136. Over time, element agent 132 may store a plurality of records containing provisioning information 140 and correlated monitored information 142 associated with particular time periods. In a particular embodiment, these records can collectively form correlation history 136.

The street and street the street that the street the street that the street that the street that the street the street that th

5

10

15

20

25

30

One or more applications 150 access information in memory 134 to track and/or manage the performance of element 110. As one particular example, application 150 may comprise a graphical user interface (GUI) operable to display one or more sets of correlated provisioning information 140 and monitored information 142. This may facilitate, for example, inspection of provisioned and operational characteristics of element 110 to identify trends in operation, to identify a malfunctioning component of element 110, to facilitate optimization of operation, or various other utilities.

As another example, application 150 could comprise a benchmarking application operable to facilitate "before and after" comparisons to assess the impact of a change in provisioning to the operation of element 110.

As still another example, application 150 could comprise a trouble shooting application operable to identify improper or inefficient provisioning settings in For example, trouble shooting application element 110. 150 could index correlation history 136 using monitored representing desired operational information information characteristics to identify provisioning previously correlated with those characteristics. provisioning information could represent a provisioning produce desirable operational state known to Application 150 can then compare the characteristics. retrieved provisioning information 140 with the current element settings to facilitate identification of problems with and/or modification of the provisioning of element 110 so that its operation can more closely approximate the desired state of operation.

The state of the s

5

10

15

20

25

30

application As a related example, 150 could facilitate reversion provisioning. For example, correlation history 136 may store a set of provisioning information 140, which is known based, for example, on past experience to yield desired results. By indexing history 136 using of correlation а portion provisioning information and one or more operational characteristics, the remaining provisioning information associated with the desired operating characteristics can be recalled.

As a particular example, one set of provisioning and monitored information information 140 142 mav identify pump power levels, pre-emphasis levels, and/or amplifier gain levels associated with a particular number of channels and particular operational characteristics. As the number of channels processed by element 110 changes over time, provisioning information associated with the element may also change. When the number of channels returns to its original state, a reversion provisioning application 150 can facilitate automatically reverting to the set of provisioning information previously used by element 110 when dealing with that particular number of channels. This can eliminate quesswork and inefficiency associated with trying to recreate that set of provisioning information based on a trial and error approach. By, for example, searching correlation history 136 for provisioning information 140 containing a desired number of channels, and possibly correlated with a desired output characteristic, reversion provisioning application can apply all or a part of the retrieved provisioning

10

15

20

25

30

17

information 140 to revert element 110 to previously approved element settings.

These are just a few examples of advantageous uses of correlation history 136 in system 100. Various other uses of this information fall within the spirit and scope of this invention.

FIGURE 3 is a block diagram of one example of a correlation history 236 associated with a particular optical element, for example, optical element 110 described with respect to FIGURE 2. In this example, correlation history 236 includes a plurality of records 210a-210n. Each record includes provisioning information 240 and monitored information 242 associated with element 110 at a particular time 250.

Provisioning information 250 may include, example, information regarding channel pre-emphasis used in element 110 as well as and the number of channels processed by element 110. Other provisioning information could be stored without departing from the scope of the invention. Monitored information 242 could include, for example, input power, mid-stage power, output power, gain tilt, optical-signal-to-noise-ratio, back reflected orany other operational characteristics associated with element 110.

In a particular embodiment, any individual piece of provisioning information 240 can be used as an index to retrieve any piece of monitored information 242 residing in the same record. Likewise, items of monitored information 242 can be used as an index to retrieve any item of provisioning information 240 from the same record 210. In addition, any piece of provisioning or monitored information could be used to access all or a portion of

of

340

|- a = THE TANK OF THE PARTY OF THE PA 1 = 1 14 [] 1,11

5

10

15

20

25

30

any other correlated information. Other arrangements and correlation schemes could be used without departing from scope of the invention. The above-described correlation is intended as just one example.

FIGURE 4 is a block diagram of a link management Link management system 300 includes an system 300. comprising a plurality optical link 320 Each optical span comprises an optical fiber 320a-320n. coupled to one or more optical elements 310. element in system 300 has associated with it a local element manager 330. Local element managers 330 are

similar in structure and function to element manager 130 described with respect to FIGURE 2. Each local element manager 330 includes an element agent 332 operable to receive provisioning information 340 and monitored information 342 from its associated element 310. Element 332

monitored information 342 in their associated memories 334.

store provisioning information

As in the embodiment shown in FIGURE 2, memories 334 may store correlation histories 336, which provisioning information 340 correlated to monitored information, 342. One or more element applications 350 and/or access memories 334 to track mav performance of individual elements 310 or combinations of elements 310.

In the illustrated embodiment, system 300 includes a 360 operable to track and/or link manager performance of one or more elements 310 and/or the entire optical link 320. In this example, link manager 360 includes a manager agent 362 operable to receive provisioning and monitored information from each of

10

15

20

25

30

elements 310. Manager agent 362 may receive this information, for example, through each element agent 332 querying elements 310, or may obtain information already queried or otherwise received from elements 310 and stored in element memories 334. Link manager 360 also includes one or more memories 364. Memory 364 stores information associated with each element 310 in optical link 320.

Link manager 360 may also receive information from adaptation module 370. Adaptation module 370 comprises hardware, software, and/or firmware operable to facilitate retrieval of provisioning and/or monitored information of various manufacturers' equipment. For example, equipment interfacing with adaptation module 370 may provide provisioning and/or monitored information in a format other than the format typically used by link manager 360. Adaptation module 370 operates to reformat the information received so that it can be assimilated and/or correlated with other information associated with optical link 320.

Link manager 360 may further include one or more and/or applications 365 operable to track manage operation of elements 310 and/or optical link 320 based provisioning information least in part on at monitored information associated with those elements. Application 365 may obtain such information, for example, from records residing in manager memory 364. Application all of the may provide some or functions application 150 described with respect to FIGURE 2. addition, application 365 may facilitate tracking and/or managing the operation of optical link 320.

10

15

20

25

30

For example, application 365 mav facilitate identifying a malfunctioning component in one or more elements 310 by examining the operation of optical link As a particular example, a pump driving one of an including amplifier may be weakening. element an 365 may compare various characteristics Application associated with elements in optical link 320 to identify the weakening amplifier pump. Application 365 may, for example, compare input powers to each amplifier and pump powers driving each amplifier to determine the location of a weakening pump.

In one case, application 365 may determine that a particular element 310b is receiving an appropriate power level input signal, but exhibiting a high drive current to its laser pump. This indicates that the driving source associated with element 310b is likely weakening. In another case, application 365 may determine although element 310b has an abnormally high pump power, the input signal to element 310b is abnormally low. could indicate, for example, a malfunction in the previous amplifier 310a in that span, or a fault in optical span 320b between elements 310a and 310b. 300 facilitates pinpointing the location of a malfunction in an optical link by facilitate simultaneous analysis of characteristics associated with a number of elements 310 along optical link 320.

In this example, link manager 360 includes an interface 380, which facilitates an external application 390 accessing and retrieving information from manager memory 364. External application 390 may comprise a module remote from optical link 320, which is operable to access provisioning and monitored information associated

10

15

20

25

30

ATTORNEY DO T NO. 069204.0108

with link 320 and to facilitate tracking and/or management of elements 310 and/or optical link 320. Interface 380 could provide security features to protect correlation histories 364 from unauthorized access by external entities.

21

In this particular example's operation, link 320 receives optical signals at an element 310a comprising an optical signals which amplifies the amplifier, communicates them toward the next element 310. Element 332 associated with each element 310 agents may periodically, on a random basis, or on command receive or retrieve provisioning and monitored information from one or more elements 310. Element agents 332 store the provisioning and correlated monitored information correlation histories 336 of memories 334. Manager agent 362 on demand, on a periodic basis, or on a random basis, retrieves provisioning and and monitored information associated with each element 310 and stores that information in manager memory 364. Manager applications 365 and/or external applications 390 track and/or modify the operation of elements 310 and/or optical links 320 based at least in part on provisioning associated and monitored information with those amplifiers.

FIGURE 5 is a block diagram showing one example of a multiple link management system 400. Multiple management system 400 includes a system manager 460 operable to track and/ or manage one or more optical links in system 400. System manager 460 is similar in structure and function to link manager 360 shown FIGURE 4, and has capabilities of managing numerous optical links 420a-420n.

10

15

20

25

30

462 System manager comprises a manager agent operable to receive provisioning and monitored information from numerous elements in one or more optical Manager agent 462 can receive this links 420a-420n. information, for example, through each element agent 432 querying elements 410, or may obtain information already queried or otherwise received from elements 410 and stored in element memories 434. System manager 460 also includes one or more memories 464a-464n. Memories 464a-464n could be physically separate storage devices, or could comprise logically partitioned regions of one or more common memory devices. Each memory 464 stores information associated with each element 410 in its associated optical link 420.

System manager 460 may also receive information from adaptation module 470. Adaptation module 470 comprises hardware, software, and/or firmware operable to facilitate retrieval of provisioning and/or monitored information of various manufacturers' equipment. For example, equipment interfacing with adaptation module 470 may provide provisioning and/or monitored information in a format other than the format typically used by link manager 460. Adaptation module 470 operates to reformat the information received so that it can be assimilated and/or correlated with other information associated with optical link 420.

Link manager 460 may further include one or more element applications 465a-465n operable to track and/or manage operation of elements 410 and/or optical links 420 based at least in part on provisioning information and monitored information associated with those elements and/or links. Applications 465 may provide some or all

10

15

20

25

30

of the functions of application 150 described with respect to FIGURE 2. In addition, application 465 may facilitate tracking and/or managing the operation of optical links 420a-420n individually, or in combination with one another.

FIGURE 6 is a flow chart illustrating one example of a method 500 of managing one or more optical elements. To provide one particular example, method 500 will be described with primarily with respect to management system 100 shown in FIGURE 2. Other management systems managing different types of optical elements could implement method 500 without departing from the scope of the invention.

In this example, method 500 begins at step 510 where system 100 stores provisioning information 140 in element System 100 can obtain provisioning 134. information 140, for example, by using query module 133 to query element 110 on command, periodically, or on a random basis to obtain provision information 140. similar manner, system 100 stores monitored information 142 in memory 134. Element agent 132 could, for example, implement query module 133 to retrieve monitored information 142.

Element agent 132 maintains a correlation history 136 at step 530. Correlation history 136 comprises a plurality of correlated values of provisioning monitored information information 140 and Correlation history 136 provides a historical view of the in which monitored information 142 varies as provisioning information 140 changes. In addition, correlation history 136 can show the way monitored

10

15

20

25

30

information 142 can change over time even though provisioning information 140 remains constant.

In this example, element agent 132 accesses memory 134 at step 540 to retrieve correlated provisioning and monitored information. Element agent 132 applies at least a portion of the retrieved correlated information application 150 at step 550. As particular non-limiting examples, application 150 can operate to display correlated information to users, or may analyze this information to facilitate modifying the operation of element 110. For example, application 150 may retrieve provisioning information from correlation history 136 by indexing correlation history 136 with a known value of monitored information 142 corresponding to a desired state of operation. Application 150 can then compare the retrieved provisioning information with provisioning information currently associated with element 110 determine changes that need to be made provisioning of element 110 to result in the desired state of operation.

As another example, application 150 could perform reversion provisioning. As one example of reversion provisioning, application 150 could index correlation history 136 using one portion of provisioning information 140 to obtain a full set of provisioning information associated with that portion and possibly also associated with a desired state of operation.

Although this example has been described with respect to managing a single element 110, method 500 can equally apply to management of multiple elements in a single optical link, or to managing multiple optical links. Systems shown in FIGURES 4 and 5 provide two

10

ATTORNEY DO T NO. 069204.0108

non-limiting examples of systems that could implement method 500.

Although the present invention has been described in several embodiments, a myriad of changes, variations, alterations, transformations, and modifications may be suggested to one skilled in the art, and it is intended that the present invention encompass such changes, variations, alterations, transformations, and modifications as fall within the spirit and scope of the appended claims.